






Can Carrier Applicator Matrix



Feature/Specification	CCA120/180	CCA440	CCA875	MPA30i Flex
CPM Quadpack/Sixpack	120/180	440 with 15% surge	875 with 10% surge	720
Standard Cans	✓	✓	✓	✓
Sleek Cans	✓	✓	✓	✓
Slim Cans	✓	✗	✗	✗
Tool-less Change Over Between Can Sizes	✗	✗	✗	✓
12 oz, 16 oz, 19.2 oz Compatible	✓	✓	✓	✓
Dual Lane	✓	✓	✓	✗
Application In Case Format	✗	✗	✗	✓
Bypass Mode	✓	✓	✓	✓
Intermittent or Continuous Motion	Intermittent	Continuous Motion	Continuous Motion	Intermittent
HMI Touch Screen w/Status-IO-Alarm Msg	✓	✓	✓	✓
UL Listed Industrial Controls Enclosure	✓	✓	✓	✓
CE Certified Machine	Option	Option	Option	Option
Category III-PLD Safety System	✓	✓	✓	✓
Remote Connectivity/Support	✓	✓	✓	✓
Fully Welded Brushed Stainless Steel Frame	✓	✓	✓	✓
Allen Bradley Machine Control Components	✓	✓	✓	✓
Power Requirements	120V Single Phase	480V/3phase/60hz	480V/3phase/60hz	480V/3phase/60hz
Dimensions	42WX90LX49H	45WX140LX86H	48Wx192Lx93H	88WX120LX92H
Weight	1225	2800	4000	3800